

jGun® DUAL SPEED Pneumatic Torque Tool

The jGun® DUAL SPEED is the only pneumatic multiplier that gives you the flexibility to use it for rundown, final torque, and heavy duty breakout. For fast rundown and powerful torque capability, the jGun® DUAL SPEED is the industry's most reliable choice.

WHEEL GUN ACCESSORY



The Wheel Gun Accessory is the obvious choice for wheel bolting and all nuts and bolts in confined spaces. The powerful extension system delivers the desired torque without compromise to power or durability. With industry-leading repeatability and intuitive design, job integrity is always assured.

3-IN-1 BOLTING SYSTEM




A simple twist of the collar switches the tool from high speed rundown mode into the max power mode with adjustable torque so you can choose the right output for your job.

INTUITIVE DESIGN



This robust tool eliminates the need for multiple systems making training simpler and reducing the chance for operator error. When multiple systems are used to assemble a bolted joint there is more chance for operator error. The jGun® DUAL SPEED makes the job simpler by giving operators one easy to use system that can be used from start to finish.



LEGEND: H = HEIGHT	L = LENGTH D = OUTER DIAMETER OF GEARBOX DC = DIAMETER OF COLLAR
---------------------------	---

MODEL NUMBER	н	L	D	DC	SQUARE DRIVE	WEIGHT	TORQUE		RPM	
IMPERIAL	in.					lbs.	ft-Ibs (Min)	ft-lbs (Max)	High	Low
J - A.5 - AP	7.32	8.07	2.58	2.99	0.75	9.04	194	502	465	24.0
J - A1 - AP	7.40	10.55	2.58	2.99	0.75	9.70	312	1,272	126	6.5
J - A2 - AP	8.42	12.51	3.25	4.48	1.00	15.00	520	2,039	97	5.0
J - A3 - AP	7.50	12.48	3.19	2.99	1.00	12.00	830	3,072	39	2.0
J - A5 - AP	8.42	14.65	4.15	4.48	1.50	22.50	1,215	5,007	48	2.5
J - A8 - AP	8.46	15.38	4.56	4.48	1.50	28.75	2,079	8,285	29	1.5

METRIC	mm					kg	Nm (Min)	Nm (Max)	High	Low
J - A.5 - AP	186	205	66	76	19	4.11	263	680	465	24.0
J - A1 - AP	188	268	66	76	19	4.41	423	1724	126	6.5
J - A2 - AP	214	318	83	114	25	6.82	705	2763	97	5.0
J - A3 - AP	191	317	81	76	25	5.45	1125	4163	39	2.0
J - A5 - AP	214	372	105	114	38	10.23	1646	6785	48	2.5
J - A8 - AP	215	391	116	114	38	13.07	2817	11226	29	1.5

The World's Most Trusted Industrial Bolting Systems



Headquarters: 333 Route 17 N., Mahwah, NJ 07430 +1-201-512-9500

Phone: 1-800-FOR-HYTORC

Email: info@hytorc.com

Online: hytorc.com